

<b>AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT</b>			1. CONTRACT ID CODE N/A		PAGE 1 OF 2 PAGES		
2. AMENDMENT/MODIFICATION NO. 0010		3. EFFECTIVE DATE APR. 19 2002		4. REQUISITION/PURCHASE REQ. NO. N/A		5. PROJECT NO. (If applicable) SPEC. NO. 1249	
6. ISSUED BY CODE		7. ADMINISTERED BY (If other than Item 6) CODE					
DEPARTMENT OF THE ARMY U.S. ARMY ENGINEER DISTRICT, SACRAMENTO SACRAMENTO, CALIFORNIA 95814-2922				DISTRICT ENGINEER U.S. ARMY ENGINEER DISTRICT, SACRAMENTO 1325 J STREET SACRAMENTO, CALIFORNIA 95814-2922 ATTN: CONTRACTING DIVISION			

8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)		(✓)	9A. AMENDMENT OF SOLICITATION NO. DACA05-02--R-0004
		×	9B. DATED (SEE ITEM 11) N/A
			10A. MODIFICATION OF CONTRACTS/ORDER NO. N/A
			10B. DATED (SEE ITEM 13) N/A
CODE	FACILITY CODE		

**11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS**

☒ The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offers ☐ is extended, ☒ is not extended.

Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods:

(a) By completing Items 8 and 15, and returning 1 copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.

12. ACCOUNTING AND APPROPRIATION DATA (If required)  
N/A

NOTE: ITEM 13 BELOW IS N/A.

**13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS, IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.**

(✓)	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A. N/A
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:
	D. OTHER (Specify type of modification and authority) N/A

**E. IMPORTANT:** Contractor ☐ is not, ☐ is required to sign this document and return \_\_\_\_\_ copies to the issuing office.

14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)

FY02 REPLACEMENT ARMY FAMILY HOUSING  
WNR PP WEST/P1  
Fort Huachuca, Arizona

1 Encl.

1. Revised Pages: 01011-24

Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.

15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
15B. CONTRACTOR/OFFEROR  (Signature of person authorized to sign)	15C. DATE SIGNED	16B. UNITED STATES OF AMERICA BY (Signature of Contracting Officer)	16C. DATE SIGNED

**TABLE 2-10 - HARDWARE SPECIFICATIONS**

<b>Hardware Type/ Specification</b>	<b>Specific Requirements</b>
Hinges BHMA 101	Hinges shall be 102 mm x 102 mm [4 in x 4 in] at exterior doors, and 90 mm x 90 mm [3-1/2 in x 3-1/2 in] at interior doors.
Self-closing Spring Hinges ANSI 156-17	Single-acting Grade 2, spring pivot stainless steel
Locks & Latches BHMA 601	Series 4000, Grade 2, at exterior doors. Grade 2 or 3 at interior doors. Provide trim of wrought brass, aluminum, or stainless steel.
Auxiliary Locks BHMA 501	Series 4000, Grade 2. Provide matching trim of wrought brass, aluminum, or stainless steel.
Interconnected Lock & Latches BHMA 611	Grade 2. Provide matching trim of wrought brass, aluminum, or stainless steel.
Closers BHMA 301	Series CO2000, Grade 2.

2.q.(1). Locks and keys. Lock cylinders shall have six pin tumblers and interchangeable cores. The Contractor shall coordinate core changes with the User after acceptance of the dwelling units. Provide a master keying system. Locks for each housing unit, including exterior storage and garage door(s), shall be keyed alike. Mechanical Room door shall be keyed separately from the tenant key. Locks and keys shall conform to the standards and requirements of the Builders Hardware Manufacturers Association (BHMA) listed above. Keying must be **integrated with existing** "Best" system.

2.q.(2). Weather-stripping and exterior thresholds. Provide nonferrous metal or vinyl weather-stripping for all housing unit exterior doors (including those from garage and exterior bulk storage). Vinyl magnetic weather-stripping is acceptable for metal doors. Exterior thresholds shall be nonferrous metal. Design of the exterior threshold at slab shall be unacceptable if wood or other material subject to deterioration is used with the concrete slab.

2.q.(3). Applications. Locks and hinges shall be applied as follows:

2.q.(3).(a). Exterior hinged entrance doors shall have 1-1/2 pair of hinges, lockset, and an auxiliary lock or interconnected lock and latch. Each windowless entrance door will have a viewer mounted at eye level.

2.q.(3).(b). Exterior bulk storage door shall have 1-1/2 pair of hinges and lockset.

2.q.(3).(c). Interior doors shall have one and one half pair of hinges and latchset with BHMA 601, F75 or F76 operations.

2.q.(3).(d). Doors in fire-rated walls from housing unit to garage shall have one of ball-bearing hinge, two self-closing spring hinges, lockset, auxiliary lock or interconnected lock and latch.

2.q.(3).(e). Garage side exterior doors shall have 1-1/2 pair of hinges and lockset.

2.r. Mailboxes. All housing units shall be provided with community mailboxes. Mail receptacles shall conform to criteria in USPS Publication 17 and 13, as appropriate. 152 mm {6 inches} thick concrete slabs shall be provided to support Centralized Mail Delivery Units. Each Centralized Mail Delivery Unit shall consist